

EPOSYST SL Flake Deco

Pigmented two-component solvent-free epoxy resin flooring system with densely broadcasted of colour chips

Total thickness	≥ 1,5-2,5 mm
Uses	educational sites, hospitals, exhibition halls, offices corridors, archives, sales halls

FeRFA type 5

Consumption ca:

Primer	EPOKATE KRUNT, transparent, EP, 2-component, solvent- and nonylphenol free	0,3-0,4 kg/m ²
---------------	--	---------------------------



broad casting

Fire dried silica sand \varnothing 0,1-0,3 mm

0,8-1,0 kg/m²

Optional / Scratch primer up to 1 mm depth of roughness:

Scratch primer (optional)	EPOKATE KRUNT, transparent, EP, 2-component, solvent- and nonylphenol free	0,6-0,8 kg/m ²
----------------------------------	--	---------------------------



filler

Fire dried silica sand \varnothing 0,1-0,3 mm

0,2-0,25 kg/m²



broad casting

Fire dried silica sand \varnothing 0,1-0,8 mm

0,8-1,0 kg/m²

Self-levelling coat	EPOKATE SL, pigmented, EP, 2-component solvent- and nonylphenol free, glossy	1,0 kg/m ²
----------------------------	--	-----------------------



filler (optional)

Fire dried silica sand \varnothing 0,1-0,3 mm

0-0,5 kg/m²



densely

Disboxid Multicolor flakes

0,5-0,7 kg/m²

decorative scatter

Sealer	PUR Aqua Top 2K, SG, 2-component water based PUR sealer	0,2 kg/m ²
---------------	---	-----------------------

Notes:

PUR Top TX produced by Remmers Bauchemie GmbH.

Disboxid Multicolor produced by CAPAROL Farben Lacke Bautenschutz GmbH.