

## EPOSYST HM

### Two-component multi purpose highly filled lightly textured epoxy mortar screed

**Total thickness** ≥ 4-6 mm

**Uses** slippery production sites, food production areas, warehouses, storage halls, maintenance hangars, washrooms and garages, production corridors, loading ramps, agricultural facilities

FeRFA type 6

Consumption ca:

<b>Primer</b>	EPOKATE KRUNT, transparent, EP, 2-component, solvent- and nonylphenol free	0,3-0,4 kg/m <sup>2</sup>
---------------	--	---------------------------



broad casting

Fire dried silica sand ø 1-1,8 mm

0,8-1,0 kg/m<sup>2</sup>

<b>Trowelled layer</b>	EPOKATE HM, transparent, EP, 2-component solvent- and nonylphenol free	215 g/m <sup>2</sup> /mm
------------------------	--	--------------------------



filler

Coloured quarz sand ø 0,8-1,2 mm or 1-1,8 mm

1,8 kg/m<sup>2</sup>/mm

<b>Topping varnish</b>	EPOKATE LAKK or EPOKATE LAKK-3 transparent, EP, 2-component, solvent- and nonylphenol free, glossy	1,2 kg/m <sup>2</sup>
------------------------	--	-----------------------

#### Notes:

Spread the trowelled screed mix on the substrate by squeegee box or by hand with a squeegee that ensures uniform layer thickness. Pack the applied trowelled screed with a hand trowel or a special power rotary trowel machine (e.g. Scanmaskin).