

## EPOSYST COMPACT

### Two-component multi purpose highly scattered textured epoxy screed

Total thickness  $\geq 2-4$  mm

Uses **slippery production sites, food production areas, warehouses, storage halls, maintenance workshops, washrooms and garages, production corridors, loading ramps, agricultural facilities**

FeRFA type 4

Consumption ca:

<b>Primer</b>	EPOKATE KRUNT, transparent, EP, 2-component, solvent- and nonylphenol free	0,3-0,4 kg/m <sup>2</sup>
---------------	--	---------------------------



broad casting	Fire dried silica sand $\varnothing 0,1-0,3$ mm	0,8-1,0 kg/m <sup>2</sup>
---------------	---	---------------------------

Optional / Scratch primer up to 1 mm depth of roughness:

<b>Scratch primer (optional)</b>	EPOKATE KRUNT, transparent, EP, 2-component, solvent- and nonylphenol free	0,6-0,8 kg/m <sup>2</sup>
----------------------------------	--	---------------------------



filler	Fire dried silica sand $\varnothing 0,1-0,3$ mm	0,2-0,25 kg/m <sup>2</sup>
--------	---	----------------------------



broad casting	Fire dried silica sand $\varnothing 1-1,8$ mm	0,8-1,0 kg/m <sup>2</sup>
---------------	---	---------------------------

<b>Scratching layer</b>	EPOKATE HM, transparent, EP, 2-component solvent- and nonylphenol free	0,6-0,8 kg/m <sup>2</sup>
-------------------------	--	---------------------------



filler	Fire dried silica sand $\varnothing 0,1-0,3$ mm	0,2-0,3 kg/m <sup>2</sup>
--------	---	---------------------------



broad casting	Coloured quartz sand $\varnothing 0,4-0,8$ mm or $0,8-1,2$ mm	2,5-3,0 kg/m <sup>2</sup>
---------------	---	---------------------------

<b>Topping varnish</b>	EPOKATE LAKK or EPOKATE LAKK-3 transparent, EP, 2-component, solvent- and nonylphenol free, glossy	0,8-1,2 kg/m <sup>2</sup>
------------------------	--	---------------------------