

## EPOSYST KP

### Two-component multi purpose highly filled with gravel textured epoxy mortar screed

**Total thickness** ≥ 6-12 mm

**Uses** external stairs, loading ramps, sales halls, bath and shower rooms, saunas, exhibition halls

**FeRFA type 6**

Consumption ca:

<b>Primer</b>	EPOKATE KRUNT, transparent, EP, 2-component, solvent- and nonylphenol free	0,3-0,4 kg/m <sup>2</sup>
---------------	--	---------------------------



broad casting

Fire dried silica sand ø 1-1,8 mm

0,8-1,0 kg/m<sup>2</sup>

<b>Scratching layer</b>	EPOKATE HM, transparent, EP, 2-component solvent- and nonylphenol free	215 g/m <sup>2</sup> /mm
-------------------------	--	--------------------------



filler

Coloured quarz gravel ø 2-4 mm or 4-6 mm

1,8 kg/m<sup>2</sup>/mm

<b>Topping varnish</b>	EPOKATE LAKK or EPOKATE LAKK-3 transparent, EP, 2-component, solvent- and nonylphenol free, glossy	300-320 g/m <sup>2</sup> /mm
------------------------	--	------------------------------

<b>Sealer (optional)</b>	PUR Aqua Top 2K, SG, 2-component water vased PUR sealer	0,2 kg/m <sup>2</sup>
--------------------------	---	-----------------------

Notes:

PUR Top TX produced by Remmers Bauchemie GmbH.