

Safety Data Sheet has been compiled according to Regulation (EC) No 1907/2006 (REACH), Annex II

Revision date: 1.11.2015  
Previous version: -  
Valid from: 1.11.2015

## MATERIAL SAFETY DATA SHEET "EPOKATE LAKK3" (B)

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

EPOKATE LAKK (B)

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses:

Epokate LAKK3 (B) is used as hardener in two-component epoxy-resin flooring systems, mainly as coating material. It is intended for professional use at construction sites and for conditions which need to endure heavy load of wearing or friction (e.g. production halls, warehouses, airplane hangars, garages, laboratories, farms).

#### 1.3 Details of the supplier of the safety data sheet:

Manufacturer/Distributor:

Epokate OÜ

Address:

Savimäe 5, Vahi küla, Tartu vald, 60534, Tartumaa, Estonia

Telefoninumber:

+ 372 50 83 751

E-posti aadress:

info@epokate.ee

#### 1.4 Emergency telephone number:

Poisoning information centre:

16662 (24-hour emergency response hotline)

Rescue:

112 (24-hour emergency response hotline)

### SECTION 2: Hazards identification

*Classification & labelling according to REGULATION (EC) No 1272/2008*

#### 2.1 Classification of the substance or mixture:

Acute Tox 4; H302  
Acute Tox 4; H332  
Skin Corr. 1B; H314  
Eye Dam. 1; H318  
Skin Sens.; H317  
Aquatic Chronic 3; H412

#### 2.2 Label elements:

Hazard pictograms:



Signal word:

**WARNING**

Hazard statements:

H302 - Harmful if swallowed.  
H332 - Harmful if inhaled.  
H314 - Causes severe skin burns and eye damage.  
H318 - Causes serious eye damage.  
H317 - May cause an allergic skin reaction.  
H412 - Harmful to aquatic life with long lasting effects.

**EUH071 - Corrosive to the respiratory tract.**

**EUH210 - Safety data sheet available on request.**

Precautionary statements:

P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.

P202 - Do not handle until all safety precautions have been read and understood.

P310 - Immediately call a POISON CENTER or doctor/physician.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P273 - Avoid release to the environment.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P301+P330+P331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P501 - Dispose of contents/container in accordance with local/regional/national/international regulations

*Full text of H-, P- and EUH phrases: see SECTION 16*

### 2.3 Other hazards:

The mixture does not contain PBT or vPvB substances according to REGULATION (EC) No 1907/2006 Annex XIII criteria

## SECTION 3: Composition/information on ingredients

**3.1 Substances:** not applicable, see point 3.2

**3.2 Mixtures:**

Description of the mixture:

Mixture is used as component B for two-component epoxy flooring systems. Prior to use mix together with epoxy resin (component A)

Hazardous ingredients:

| Substance name   | CAS no.     | REACH registration number | Concentration % | Classification according to REGULATION (EC) No. 1272/2008                          |                                      |
|--|-------------|---------------------------|-----------------|--|--------------------------------------|
| Benzyl alcohol   | 100-51-6    | 01-2119492630-38          | 30-60           | Acute Tox. 4<br>Acute Tox. 4   | H302<br>H332                         |
| m-phenylenebis(methylamine)  | 2855-13-2   | 01-2119514687-32          | 13-30           | Acute Tox. 4<br>Acute Tox. 4<br>Skin Corr. 1B<br>Skin Sens. 1                      | H302<br>H312<br>H314<br>H317         |
| 4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with m-phenylenebis(methylamine) | 113930-69-1 | 01-2119965162-39          | 13-30           | Acute Tox. 4<br>Skin Corr. 1B<br>Skin Sens. 1<br>Acute Tox. 3<br>Aquatic Chronic 3 | H302<br>H314<br>H317<br>H331<br>H412 |
| m-phenylenebis(methylamine)  | 1477-55-0   | 01-2119480150-50          | 7-13            | Acute Tox. 4<br>Eye Dam. 1   | H302<br>H318                         |
| Salicylic acid   | 69-72-7     | 01-2119486984-17          | 1-3             | Acute Tox. 4<br>Eye Dam. 1   | H302<br>H318                         |

*Full text of H- and EUH-phrases: see SECTION 16*

*There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs or vPvBs or have been assigned a workplace exposure limit and hence require reporting in this section. Occupational exposure limits, if available, are listed in SECTION 8.*

**SECTION 4: First aid measures****4.1 Description of first aid measures:**

|  |  |
|--|--|
| <u>Inhalation:</u>                         | Supply fresh air and call for doctor for safety reasons. In case of unconsciousness bring patient into stable side position for transport.   |
| <u>Skin contact:</u>                       | Instantly wash with water and soap and rinse thoroughly.<br>Cover wound with a sterile dressing.<br>If skin irritation continues, consult a doctor.  |
| <u>Eye contact:</u>                        | Rinse opened eye for several minutes under running water. Then consult doctor. Continue to bathe eyes during transport to medical practitioner.  |
| <u>Ingestion:</u>                          | Rinse out mouth and then drink plenty of water. Call a doctor immediately.<br>Do not induce vomiting unless directed to do so by medical personnel.<br>Maintain an open airway. Seek immediate medical attention.  |
| <u>Self-protection of the first aider:</u> | Take affected persons out of danger area and instruct to lie down.<br>Instantly remove any clothing soiled by the product. No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. |

**4.2 Most important symptoms and effects, both acute and delayed**

|                      |  |
|----------------------|--|
| <u>Eye contact:</u>  | Corrosive to eyes. Symptoms may include pain, watering, redness.   |
| <u>Inhalation:</u>   | Harmful by inhalation. May give off gas, vapour or dust that is very irritating or corrosive to the respiratory system. Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure. |
| <u>Skin contact:</u> | Corrosive to the skin. Causes burns. Harmful in contact with skin. May cause sensitization by skin contact. Adverse symptoms may include irritation or pain, redness, blistering may occur.  |
| <u>Ingestion:</u>    | Harmful if swallowed. May cause burns to mouth, throat and stomach. Adverse symptoms may include stomach pains.  |

**4.3 Indication of any immediate medical attention and special treatment needed**

|                              |  |
|------------------------------|--|
| <u>Notes for the doctor:</u> | Contact poison treatment specialist immediately if large quantities have been ingested or inhaled. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. |
| <u>Special treatment:</u>    | No specific treatment.   |

**SECTION 5: Fire fighting measures****5.1 Extinguishing media:**

|  |  |
|--|--|
| <u>Suitable extinguishing media:</u>   | Use dry chemical. CO <sub>2</sub> , extinguishing powder or water spray (fog). |
| <u>Unsuitable extinguishing media:</u> | Water with a full water jet.   |

**5.2 Special hazards arising from the substance or mixture:**

In a fire or if heated, the pressure increase may cause the container to burst. Decomposition product may include carbon dioxide, carbon monoxide, nitrogen oxides.

### 5.3 Advice for firefighters:

Special protective actions for fire-fighter:

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. This material is toxic to aquatic organisms. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Special protective equipment for fire-fighters:

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

Additional information:

In case of fire cool endangered containers with water.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders

If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also Section 8 for additional information on hygiene measures.

### 6.2 Environmental precautions:

Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

### 6.3 Methods and materials for containment and cleaning up:

Small spill:

Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container.

Large spill:

Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with noncombustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13).

### 6.4 References to other sections:

See **Section 1** for emergency contact information. See **Section 8** for information on appropriate personal protective equipment. See **Section 13** for additional waste treatment information.

## SECTION 7: Handling and storage

### 7.1 Conditions for safe storage, including any incompatibilities

Protective measures:

Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Avoid release to the environment. Refer to special instructions/safety data sheet. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous.

Advice on general occupational hygiene:

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

**7.2 Conditions for safe storage, including any incompatibilities**

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

**7.3 Special end use(s)**

Recommendations: Not available

Industrial sector specific solutions: Not available

**SECTION 8: Exposure controls/personal protection****8.1 Control parameters**

Occupational exposure limits: No exposure limit value known. **Recommended monitoring procedures:** If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to European Standard EN 689 for methods for the assessment of exposure by inhalation to chemical agents and national guidance documents for methods for the determination of hazardous substances.

Derived effect levels: No DELs available

Predicted effect concentrations: No PECs available

**8.2 Exposure controls**

Appropriate engineering controls: Good general ventilation should be sufficient to control worker exposure to airborne contaminants. If this product contains ingredients with exposure limits, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

Individual protection measures:

Eye/face protection: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts.

Hygiene measures: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing.

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Reference number EN 374. Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves. (0,4 mm), breakthrough time 30 min.

Body protection: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Recommended: Use barrier skin cream.

Other skin protection: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection: No special measures required

Environmental exposure controls: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

|  |                           |
|--|---------------------------|
| Physical state                               | Liquid                    |
| Colour                                       | Yellowish                 |
| Odour  | Amine-like                |
| Odour threshold                              | Not available             |
| pH   | 11 (ISO 8975)             |
| Melting point/freezing point                 | Not available             |
| Initial boiling point and boiling range      | 175 °C                    |
| Boiling point                                | Not available             |
| Flash point                                  | 117 °C                    |
| Evaporation rate                             | Not available             |
| Flammability (solid, gas)                    | Not available             |
| Burning time                                 | Not available             |
| Burning rate                                 | Not available             |
| Upper/lower flammability or explosive limits | Not available             |
| Vapour pressure                              | Not available             |
| Vapour density                               | <0,002 kPa                |
| Density                                      | Not available             |
| Relative density                             | 1,05                      |
| Solubility(ies)                              | Slightly soluble in water |
| Partition coefficient: noctanol/water        | Not available             |

|                           |                      |
|---------------------------|----------------------|
| Auto-ignition temperature | Not available        |
| Decomposition temperature | >96 °C               |
| Viscosity                 | 100-300 mPa.s (25°C) |
| Explosive properties      | Not explosive        |
| Oxidising properties      | Not available        |

## 9.2 Other information:

No additional information

## SECTION 10: Stability and reactivity

### 10.1 Reactivity:

Dangerous reactions Strong exothermic reaction with acids

### 10.2 Chemical stability:

Product is stable at normal conditions.

### 10.3 Possibility of hazardous reactions:

Under normal conditions of storage and use, hazardous reactions will not occur.

### 10.4 Conditions to avoid:

No specific data.

### 10.5 Incompatible materials:

No specific data.

### 10.6 Hazardous decomposition products:

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### **Benzyl alcohol (CAS nr 100-51-6)**

Ingestion: LD50 1030 mg/kg (rott)

Skin: LD50 1620 mg/kg (rott)

Inhalation: LC50 / 4h > 4178 mg/m<sup>3</sup> (rott)

LC50 / 8h > 1000 pm (rott)

#### Acute toxicity:

#### **m-phenylenebis (methylamine) (CAS nr 1477-55-0)**

Ingestion: LD50 930 mg/kg (rott)

Skin: LD50 >3100 mg/kg (rott)

Inhalation: LD50/ 4h 1,34 mg/l (rott)

#### **Salicylic acid (CAS nr 69-72-7)**

Ingestion: LD50 891 mg/kg (rott)

Skin: LD50 >2000 mg/kg (rott)

Corrosive

#### Irritation/Corrosion:

#### Sensitisation:

Long-term exposure may cause skin burns and allergic reactions.

#### Mutagenicity:

Not available

#### Carcinogenicity:

Not available

#### Reproductive toxicity:

Not available

Information on the likely routes of exposure: Not available

## 11.2 Other information:

Not available

## SECTION 12: Ecological information

### 12.1 Toxicity

Product has not been tested. Data is taken from properties of similar products. Harmful to fish. Harmful to aquatic organisms. May cause long-term adverse effects in the water environment. Do not allow product to reach ground water, water bodies or sewage system.

**Bensüülalkohol** EC50/48h 230 mg/l (vesikirp)  
OECD 202 Daphnia sp. Acute immobilisation Test

EgC50/72h 770 mg/l (vetikas)  
OECD 201, Algae, Growth Inhibition Test

**3-aminoetüül-  
3,5,5-trimetüül-  
tsükloheksüülamiin** EC50/48h 23 mg/l (vesikirp)  
OECD 202 Daphnia sp. Acute immobilisation Test

EC50/72h 37 mg/l (vetikas)  
EU EC C.3 Algae Inhibition Test

**4,4'-Isopropylidenediphenol,  
oligomeric reaction products  
with 1-chloro-2,3-  
epoxypropane, reaction  
products with m-  
phenylenebis(methylamine)** EL50/48h 1,46 mg/l (vesikirp)  
OECD 202 Daphnia sp. Acute immobilisation Test

EL50/72h >30 mg/l (vetikas)  
OECD 201, Algae, Growth Inhibition Test

**1,3-Bis(aminometüül) benseen;  
(m-ksüleendiamiin)** EC50/48h 15,2 mg/l (vesikirp)  
OECD 202 Daphnia sp. Acute immobilisation Test

ErC50/72h >32,1 mg/l (vetikas)  
OECD 201, Algae, Growth Inhibition Test

EC50/48h 870 mg/l (vesikirp)  
OECD 202 Daphnia sp. Acute immobilisation Test

**Salitsüülhape** EC50/72h > 100 mg/l (vetikas)  
OECD 201, Algae, Growth Inhibition Test

### 12.2 Persistence and degradability

|   |                     |  |
|---|---------------------|--|
| <b><u>Bensüülalkohol</u></b>  | 21 päevaga 95 - 97% | OECD 301 READY Biodegradability - DOC Die-away Test  |
| <b><u>3-aminoetüül-<br/>3,5,5-trimetüül-<br/>tsükloheksüülamiin</u></b> | 28 päevaga 8%       | EU EC C4-A Biodegradation: Determination of the "Ready" Biodegradability: Dissolved Organic Carbon (DOC) Die-away Test |
| <b><u>1,3-Bis(aminometüül) benseen;<br/>(m-ksüleendiamiin)</u></b>      | 28 päevaga 49%      | OECD 301B READY Biodegradability - Co2 Evolution Test  |
| <b><u>Salitsüülhape</u></b>   | 14 päevaga 88,1%    | OECD 301C Ready Biodegradability - Modified MITI TEST  |

### 12.3 Bioaccumulative potential

Slightly

### 12.4 Mobility in soil

Not available

### 12.5 Results of PBT and vPvB assessment

Not available



## 12.6 Other adverse effects

No known significant effects or critical hazards

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

|                             |   |
|-----------------------------|---|
| <u>Methods of disposal:</u> | Before disposal see information in SECTION 7 and SECTION 8. The generation of waste should be avoided or minimised wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. |
| <u>Hazardous waste:</u>     | Yes. Waste code 08 01 11* - waste paint and varnish containing organic solvents or other dangerous substances (EU waste catalogue)  |
| <u>Packaging:</u>           | Completely emptied packaging or practically empty packaging containing dried/cured residues, once relieved of all pressure can be disposed of as non-hazardous waste. Packaging may still contain hazardous residues and disposal should be undertaken by a licensed waste contractor. Any disposal practice must be in compliance with local and national laws and regulations.  |

## SECTION 14: Transport information

|  |   |
|--|---|
| 14.1 UN number:  | UN 2735   |
| 14.2 UN proper shipping name:  | Polyamines, liquid, Corrosive, n.o.s. (TeTa, EpoCure) |
| 14.3 Transport hazard class(es):   | 8   |
| 14.4 Packaging group:  | III   |
| 14.5 Environmental hazards:  | see SECTION 6   |
| 14.6 Special precautions for user:   | see SECTION 7 ja 8                                    |
| 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code: | Not applicable  |

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) 1907/2006 on the Registration, Evaluation, Authorisation and Restriction of Chemicals - REACH

Annex XIV - List of substances subject to authorisation

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Regulation (EC) 1272/2008 on the classification, labelling and packaging (CLP) of substances and mixtures - CLP

Hazardous waste & transport regulations

### 15.2 Chemical Safety Assessment

A chemicals Safety Assessment has not been done

## SECTION 16: Other information

### 16.1 Classification for mixtures and used evaluation method according to regulation (EC) 1207/2008:

| Classification according to Regulation (EC) Nr 1207/2008 | Classification procedure (Art. 9 CLP regulation) |
|--|--|
| Acute Tox. 4; H302                                       | Calculation method                               |
| Acute Tox. 4;H332  | Calculation method                               |

|                         |                    |
|-------------------------|--------------------|
| Skin Corr. 1B; H314     | Calculation method |
| Eye Dam.1; H318         | Calculation method |
| Skin sens 1; H317       | Calculation method |
| Aquatic Chronic 3; H412 | Calculation method |

## 16.2 Abbreviations and acronyms:

### Pictograms:



**GHS05**



**GHS07**

**H-phrases:** Acute Toxicity Category 4; H302  
 Acute Toxicity Category 4; H332  
 Skin Corrosive Category 1B; H314  
 Eye Damage Category 1; H318  
 Skin Sensitation Category 1; H317  
 Aquatic Chronic Category 3; H412

H312 -Harmful in contact with skin.

H332 - Harmful if inhaled.

H314 - Causes severe skin burns and eye damage.

H318 - Causes serious eye damage.

H317 - May cause an allergic skin reaction.

H412 - Harmful to aquatic life with long lasting effects.

**EUH071 - Corrosive to the respiratory tract.**

**EUH210 - Safety data sheet available on request.**

**P-phrases:** P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.  
 P202 - Do not handle until all safety precautions have been read and understood.  
 P310 - Immediately call a POISON CENTER or doctor/physician.  
 P280 - Wear protective gloves/protective clothing/eye protection/face protection.  
 P273 - Avoid release to the environment.  
 P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P301+P330+P331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting.  
 P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.  
 P501 - Dispose of contents/container in accordance with local/regional/national/international regulations